

Stampede® 4X4 (Model 67054-61) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	1647	Silicone Grease
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)	6878	Slipper clutch, complete (for Slash 4x4)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	5556 5354	Slipper pressure plate & hub (aluminum alloy)
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	5351	Slipper pressure plate and hub (alloy)
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)		Chassis & Attachments
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	6715	Body mount (1)/ body mount post (2) (front)
2545	Bushings (plastic) (5x8x2.5mm) (4)	6815R	Body mount (1)/ body mount post (2)/ body post extensions (2) (front
1985	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)		or rear)
	Body & Accessories	3628	Box, receiver (sealed)/ foam pad/2.5x8mm CS (4)/ 3x10mm CS (2)
1926	Antenna caps, vinyl (2)/ antenna spool	6735	Bumper, front/ skidplate, front (black)
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	6722	Chassis, Stampede® 4x4
3935	Body clip (mounting clip), angled, 90-degrees (10)	6727	Hold down, battery (2)/ hold down retainer/ battery post/ angled body clip
3935A	Body clip (mounting clip), angled, 90-degrees (black) (10)	6727X	Hold down, battery/ hold down retainer/ battery post/ angled
3934	Body clips, heavy duty (12)	UILIX	body clip (allows for installation of taller, multi-cell batteries)
1815	Body washers (8)	3629	Seal kit, receiver box (includes o-ring, seals, and silicone grease)
6716	Body Washers, Foam, 2mm/3mm/4mm	5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)
3617	Body, Stampede® (clear, requires painting) (requires #3614 to	4974	Wheelie Bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)
	mount)/window, lights, grill decal sheet	6777X	Wheelie bar mounts/ rear skidplate (fits 4WD Stampede®) (for LED
6729X	Body, Stampede® 4X4, blue (painted, decals applied)		light kit installation)
6711X	Body, Stampede® 4X4, ProGraphix® (Graphics are printed,	4976	Wheels (4)/ axles (2) (for T-Maxx®/E-Maxx wheelie bar)
6744	requires paint & final color application)/ decal sheet	4976	Wheels (4)/ Axles (2), for Maxx® Wheelie Bar
6714	Body, Stampede® 4x4, ProGraphix® (graphics are printed,	5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/
6729R	requires paint & final color application)/ decal sheet Body, Stampede® 4X4, red (painted, decals applied)		axles (2)/ rubber tires (2)
2514	Decal sheet, racing sponsors	5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)		axles (2)/ rubber tires (2)
5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)		Differential Components
4974	Wheelie Bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
6777X	Wheelie bar mounts/ rear skidplate (fits 4WD Stampede®) (for LED	5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
*******	light kit installation)	5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
4976	Wheels (4)/ axles (2) (for T-Maxx®/E-Maxx wheelie bar)	5381	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
4976	Wheels (4)/ Axles (2), for Maxx® Wheelie Bar	6814	Differential kit, center (complete)
5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/	6780	Differential kit, center (complete)
	axles (2)/ rubber tires (2)	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/	5136X	Differential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights)
	axles (2)/ rubber tires (2)	6882X	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
	Center Driveline		shaft, carrier support)
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)	6783	Gear set, differential (spider gears (4)/ spider gear shaft (2))
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)	6781	Housing, center differential (aluminum)/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 PTFE-coated washer/ 2.5x8
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)		CCS (4)
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	6881	Housings, differential, front
6893X	Bearing adapter, 6061-T6 aluminum (blue-anodized)	6880	Housings, differential, rear
	(1)/10x15x4mm ball bearing (black rubber sealed) (1) (for slipper	6782	Output gears, center differential, hardened steel (2)
	shaft)	5379X	Ring gear, differential/ pinion gear, differential
6893G	Bearing adapter, 6061-T6 aluminum (green-anodized) (1)/	6778	Ring gear, differential/ pinion gear, differential (12/47 ratio) (front)
	10x15x4mm ball bearing (black rubber sealed) (1) (for slipper	6779	Ring gear, differential/ pinion gear, differential (12/47 ratio) (rear)
0744	shaft)	5379R	Ring gear, differential/ pinion gear, differential (machined, spiral
6741	Cover, center driveshaft (clear)		cut) (front)
6877A	Cover, gear (clear)	6879R	Ring gear, differential/ pinion gear, differential (machined, spiral
6877 6814	Cover, gear/ motor wire hold-down clip Differential kit, center (complete)		cut) (rear)
6888	Drive hub, center, rear (1)/ 4x3 GS (1)	6879	Ring gear, differential/ pinion gear, differential (rear)
6888X	Drive hub, front, hardened steel (1)/ screw pin (1)	3965	Screws, 2.5x8mm cap-head machine (6)
6755	Drive hats, front, flatdefied steer (1) screw pin (1) Driveshaft, center, 6061-T6 aluminum (blue-anodized)	1647	Silicone Grease
6755G	Driveshaft, center, 6061-T6 aluminum (green-anodized)		Driveline Components
6755R	Driveshaft, center, 6061-T6 aluminum (red-anodized)	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
6756	Driveshaft, center, plastic (blue)/ screw pin	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
6883	Gear set, center differential (output gears (2)/ spider gears (2)/	5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
	spider gear shaft)	9059X	Cross pin (2)/ drive pin (2) (repairs 1 axle shaft)
5148	Grease, white lithium	9057X	Differential output shafts, steel-splined constant-velocity (2)
6884	Housing, center differential/x-ring gaskets (2)/ ring gear gasket/	6828A	Differential output yoke assembly, extreme heavy duty (2) (left or
	bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4)		right, front or rear) (assembled with external-splined half shaft)/
6893	Input shaft (slipper shaft)/ bearing adapter (1)/ pin (1)	000011	screw pin (2)
6890	Plate, motor	6828X	Differential output yokes, heavy duty (2)/ screw pin (2)
00001	Plate, motor, 6061-T6 aluminum (blue-anodized)	6851X	Driveshaft assembly, front, heavy duty (1) (left or right) (fully
6890X	Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum	6852A	assembled, ready to install)/ screw pin (1)
6890X 5352R		D054A	Driveshaft assembly, rear, extreme heavy duty (1) (left or right)
	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL		(fully assembled ready to install)/ screw pin (1)
5352R	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))		(fully assembled, ready to install)/ screw pin (1) Driveshaft assembly, rear, heavy duty (1) (left or right) (fully
	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (1)/	6852X	Driveshaft assembly, rear, heavy duty (1) (left or right) (fully
5352R 5352X	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	6852X	Driveshaft assembly, rear, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
5352R	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/		Driveshaft assembly, rear, heavy duty (1) (left or right) (fully
5352R 5352X	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	6852X	Driveshaft assembly, rear, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshafts, front, steel-spline constant-velocity (complete

Page 2 St	ampede® 4X4:	TQ™ 2.4GHz Rad	io (Model 67054-6	1) Parts List
-----------	--------------	----------------	-------------------	---------------

6852R	Driveshafts, rear, steel-spline constant-velocity (complete assembly) (2)	6854A	Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft)
9052X	Driveshafts, rear, steel-spline constant-velocity (complete	6854X	Stub axles, front, heavy duty (2)/ yokes (2)/ pins (4)
	assembly) (2)	6732	Suspension arm guards, front (2)/ guard spacers (2)/ hollow balls (2)/
6750	Half shaft, external splined (steel-spline constant velocity) (1)		3x18mm BCS (4)
9055X	Half shaft, external splined (steel-spline constant velocity) (1)	3655P	Suspension arms, blue, front/rear (left & right), heavy duty (2)
6751	Half shaft, internal splined (steel-spline constant velocity) (1)	3655R	Suspension arms, front/rear (left & right), heavy duty (2)
9056X	Half shaft, internal splined (steel-spline constant velocity) (1)	3655G	Suspension arms, green, front/rear (left & right), heavy duty (2)
6850X	Half shafts, heavy duty (external splined (2)/ internal splined (2))/	3655X	Suspension arms, left & right
	metal u-joints (4)	3655T	Suspension arms, orange, front/rear (left & right), heavy duty (2)
9058X	Rebuild kit, steel-splined constant-velocity driveshafts (includes	3655L	Suspension arms, red, front/rear (left & right), heavy duty (2)
	pins and hardware for one axle shaft)	6834	Suspension pin set, complete (front and rear)
6757	Rebuild kit, steel-splined constant-velocity driveshafts (includes	6898	Sway bar kit (front and rear) (includes front and rear sway bars
	pins, dustboots, lube, and hardware)		and adjustable linkage)
6854A	Stub axle assembly, front, outer, extreme heavy duty (1) (left or	6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger
	right) (assembled with internal-splined half shaft)		than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
6853A	Stub axle assembly, rear, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft)	6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
9054X	Stub axle, front, steel-splined constant velocity (1)	6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger
6754	Stub axle, front, steel-splined constant velocity (1)		than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
6753	Stub axle, rear, steel-splined constant velocity (1)	2335	Turnbuckles (72mm) (Tie rods or optional rear camber rods) (2)
9053X	Stub axle, rear, steel-splined constant velocity (1)	3643	Turnbuckles, camber link, 49mm (82mm center to center)
6854X	Stub axles, front, heavy duty (2)/ yokes (2)/ pins (4)		(assembled with rod ends and hollow balls) (1 left, 1 right)
6853X	Stub axles, rear, heavy duty (2)/pins (2)	5539	Turnbuckles, camber links, 58mm (assembled with rod ends and
6869	Wheel adaptors, 12mm hex, 6061-T6 aluminum (blue-anodized)		hollow balls) (2)
	(4)/ 3x10 screw pins (4)/ drill bit, 0.25 inch (for 6mm shafts)	6896	Wires, sway bar (front & rear, hard & soft) (Slash 4X4)/ 3x6 FCS
1654X	Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle		(4)
	pins(2)		Hardware

3690

	pins(2)
	Front Suspension & Steering
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)
6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)
6823G	Bulkhead tie bars, front & rear, aluminum (green-anodized)
6823R	Bulkhead tie bars, front & rear, aluminum (red-anodized)
2545	Bushings (plastic) (5x8x2.5mm) (4)
3641A	Camber link set (plastic / non-adjustable) (front & rear) (grey)
3641	Camber link set (plastic/ non-adjustable) (front & rear) (black)
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than Titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
6832X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right
6832G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right
6832A	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right
6832R	Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right
6832	Caster blocks (c-hubs), left & right
6845A	Drag link, machined 6061-T6 aluminum (blue-anodized)
6845G	Drag link, machined 6061-T6 aluminum (green-anodized)
6845T	Drag link, machined 6061-T6 aluminum (orange-anodized)
6845R	Drag link, machined 6061-T6 aluminum (red-anodized)
6895	Linkage, front sway bar (Slash 4x4) (2) (assembled with rod ends, hollow balls and ball studs)
6897	Linkage, rear sway bar (Slash 4x4) (2) (assembled with rod ends, hollow balls and ball studs)
6846	Linkage, steering (Revo) (3x20mm turnbuckle) (1)/ rod ends (2)/ hollow balls (2)
2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks)
2742	Rod ends, long (6)/ hollow ball connectors (6)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)
5529	Shim set, 3x7x1mm (2), 3x6x0.5mm (4), 3x7x2mm (2)/ hollow balls, captured (4)
6839	Shock tower, front
6839X	Shock tower, front, 7075-T6 aluminum (blue-anodized) (1)/ body mount bracket (1)
6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering
6837X	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right
6837G 6837A	Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left &

Steering blocks, 6061-T6 aluminum (red-anodized), left & right

Steering blocks, left & right

6837R

6837

1552 3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1) 1926 Antenna caps, vinyl (2)/ antenna spool 1726 Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	
1726 Antonna tubo (1)/ vinyl antonna can (1)/ wire retainer (1)	
1720 Antenna, tube (1)/ viriyi antenna cap (1)/ wife retainer (1)	
Attachment screws, shock (3x12mm shoulder screws) (6)	
3935 Body clip (mounting clip), angled, 90-degrees (10)	
3935A Body clip (mounting clip), angled, 90-degrees (black) (10)	
3934 Body clips, heavy duty (12)	
1589 Double-sided adhesive tape (25mm x 25mm)	
Nuts, 3mm nylon locking (12)	
1747P Nuts, 4mm flanged nylon locking (aluminum, pink anodize	d) (4)
Nuts, 4mm flanged nylon locking (steel, serrated) (8)	, , ,
1747 Nuts, 4mm nylon locking (10)	
1747R Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)
1747G Nuts, aluminum, flanged, serrated (4mm) (green-anodized)	(4)
1747T Nuts, aluminum, flanged, serrated (4mm) (orange-anodize	d) (4)
1747A Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4	·)
1985 PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearing	s)
5525 Rod ends (12)/ hollow balls (12)	
2742X Rod ends, short (6)/ hollow balls (6)	
3347 Screws, 2.5x5mm button-head machine (hex drive) (6)	
3215 Screws, 2.5x6mm cap-head machine (hex drive) (6)	
3965 Screws, 2.5x8mm cap-head machine (6)	
2577 Screws, 3x10mm button-head machine (hex drive) (6)	
2578 Screws, 3x12mm button-head machine (hex drive) (6)	
2552 Screws, 3x12mm countersunk machine (6) (hex drive)	
2579 Screws, 3x15mm button-head machine (hex drive) (6)	
2586 Screws, 3x15mm cap-head machine (hex drive) (6)	
3646 Screws, 3x15mm flat-head machine (hex drive) (6)	
2583 Screws, 3x18 button-head machine (hex drive) (6)	
2580 Screws, 3x20mm button-head machine (hex drive) (6)	
2591 Screws, 3x23mm button-head machine (hex drive) (6)	
2582 Screws, 3x30mm button-head machine (hex drive) (6)	
2592 Screws, 3x40mm button-head machine (hex drive) (6)	
2575 Screws, 3x6mm button-head machine (hex drive) (6)	
2554 Screws, 3x6mm caphead machine (hex drive) (6)	
2534 Screws, 3x6mm countersunk machine (6) (hex drive)	
3932 Screws, 3x6mm flat-head machine (hex drive) (6)	
2576 Screws, 3x8mm button-head machine (hex drive) (6)	
3931 Screws, 3x8mm flat-head machine (hex drive) (6)	
3937 Screws, 4x12mm button-head machine (hex drive) (6)	
2542 Screws, 4x12mm countersunk machine (hex drive) (6)	
2546 Screws, 4x15mm countersunk machine (hex drive) (6)	
2743 Set (grub) screws, 3mm hardened (12)	
3642X Shoulder screws, Ultra Shocks (3x12 hex drive) (6)	
2754 Stub axle pins (4)	
2746 Washers, 3x6mm metal (12)	

LED Lights

Gear set, transmission (includes idler gear (1), diff gear (1), top gear(1)) (Bandit, Rustler®, Stampede®)

Page 3 Stampede® 4X4: TQ™ 2.4GHz Radio (Model 67054-6

Page 3	Stampede® 4X4: TQ™ 2.4GHz Radio (Model 67054	-61) Parts	List
3690	LED light bar, front (assembled)/ 3x8 BCS (2)/ 2.5x8 BCS (2) (requires front bumper #5835X for 2WD Slash®, #3635 for 2WD	6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal pad
	Stampede®, #3630 for 2WD Bigfoot® No. 1, #6835X for 4WD	6519	Receiver, micro, TQ 2.4GHz (3-channel)
5893	Slash®, or #6735 for 4WD Stampede®) LED light harness, rear (requires #5838, 6737X, or 6836 rear bumper)	3932 6552	Screws, 3x6mm flat-head machine (hex drive) (6) Seal kit, expander box (includes o-ring, seals, and silicone
6794	LED light set, complete (includes front and rear bumpers with LED	6526	grease) Sensor, auto-detectable, temperature
	light bar, rear LED harness, & BEC Y-harness) (fits 4WD	6527	Sensor, auto-detectable, voltage
	Stampede®)	6520	Sensor, RPM (long)/ 3x4mm BCS (1)/ 3x4 GS (1)
2263	Y-harness, BEC to LED light set	6521	Sensor, temperature and voltage (long)
	Motors & Electronics	2254	Servo case, aluminum (middle) (blue-anodized) (for 2250 servo)
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	2253	Servo case, aluminum (middle) (red-anodized) (for 2255 servo)
2260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage)	2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)
2252	Gear set, metal (for 2250, 2255 servos)	2075R 2075	Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof
6860A	Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1)	2250	Servo, digital high-torque 300 coreless, metal gear (ball bearing), waterproof
6860R 3785	Motor mount, 6061-T6 aluminum (blue-anodized)	2255	Servo, digital high-torque 400 brushless, metal gear (ball
3765 3351R	Motor, Titan® 12T (12-Turn, 550 size) Motor, Velineon® 3500, brushless (assembled with 12-gauge		bearing), waterproof
333 H	wire and gold-plated bullet connectors)	2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof
3347	Screws, 2.5x5mm button-head machine (hex drive) (6)	6553X	Telemetry Expander 2.0 and GPS module 2.0, TQi radio system
3932	Screws, 3x6mm flat-head machine (hex drive) (6)	6550X	Telemetry expander 2.0, TQi radio system (for use only with
2254	Servo case, aluminum (middle) (blue-anodized) (for 2250 servo)		#6551X GPS module)
2253	Servo case, aluminum (middle) (red-anodized) (for 2255 servo)	6551X	Telemetry GPS module 2.0, TQi radio system (for use only with
2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for	6539	#6550X telemetry expander) Telemetry trigger magnet holder, center differential/ magnet,
	2250, 2255 servos)	0333	5x2mm (1)/ 3x8mm BCS (3) (for use with #6814 center
2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof		differential)
2075	Servo, digital high-torque (ball bearing), waterproof	6538	Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/
2250	Servo, digital high-torque 300 coreless, metal gear (ball bearing), waterproof		3x8mm CCS (3)/ 3x10mm CCS (3)
2255	Servo, digital high-torque 400 brushless, metal gear (ball	6540	Telemetry trigger magnet, 5X2mm (1)
2233	bearing), waterproof	6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link
2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof		enabled, TSM® (2-ch transmitter, 5-ch micro receiver)
3350R	Velineon® VXL-3s Brushless Power System, waterproof	6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro
	(includes VXL-3s waterproof ESC , Velineon® 3500 motor, and		receiver)
	speed control mounting plate (part #3725))	6516	Transmitter, TQ 2.4GHz, 2-channel (transmitter only)
3355R	VXL-3s Waterproof Electronic Speed Control (brushless)	6528	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-
3018R	(fwd/rev/brake) XL-5 Electronic Speed Control, waterproof (land version, low-voltage		channel (transmitter only)
30 101	detection, fwd/rev/brake)	6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-
	Radio System, Batteries & Chargers	0500	channel (transmitter only)
20.407		6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)
2842X	5000mah 7.4v 2-Cell 25C LiPo Battery	6511	Traxxas® Link Bluetooth® module
2843X 2914	5800mah 7.4v 2-Cell 25C LiPo Battery Battery, Power Cell AA Alkaline (4)	0011	
2976	AC to DC adapter		Ready-To-Race Model
2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD®	67054-61	Stampede® 4X4: 1/10-scale 4WD Monster Truck with TQ™ 2.4GHz
	batteries to separate balance ports)		radio system and LED lights
2943	Battery charge indicators, green (4), grey (4), blue (4)		Rear Suspension
6548	Battery door, TQ 2.4 transmitter (replacement for #6516, 6517	6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)
	transmitter)	6823G	Bulkhead tie bars, front & rear, aluminum (green-anodized)
2926X	Battery, Power Cell, 3000mAh (NiMH, 7-C hump, 8.4V)	6823R	Bulkhead tie bars, front & rear, aluminum (red-anodized)
2941X	Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C hump, 8.4V)	6829	Bulkhead, rear
2951X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C hump, 8.4V)	3641A	Camber link set (plastic / non-adjustable) (front & rear) (grey)
2961X 2984	Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C hump, 8.4V)	3641	Camber link set (plastic/ non-adjustable) (front & rear) (black)
2904	Battery/charger completer pack (includes #2969 2-amp NiMH peak detecting AC charger (1), #2926X 3000mAh 8.4V 7-cell NiMH iD® battery (1))	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrongh (4)/ (#075-0.2475 PGS (4)) required for installation)
2992	Battery/charger completer pack (includes #2970 iD® charger (1),	3644G	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES green-anodized, 7075-T6 aluminum,
	#2843X 5800mAh 7.4V 2-cell 25C LiPo iD® battery (1))		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
2260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage)	3644R	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
2975	Charger, D/C, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
2972	Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery		wrench (1) (#2579 3x15 BCS (4) required for installation)
	Identification	1952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (left
2973	Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification	1952G	& right)/ 3x32mm hinge pins (2)/ e-clips (6)/ hardware Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear)
2970	Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification	1952T	(left & right)/ 3x32mm hinge pins (2)/ e-clips (6)/ hardware Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear)
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery	10	(left & right)/ 3x32mm hinge pins (2)/ e-clips (6)/ hardware
0004	Identification	1952	Carriers, stub axle (rear) (2)
2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto	1952A	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (left &
CEOF	Battery Identification	CODE	right)/ 3x32mm hinge pins (2)/ e-clips (6)/ hardware
6525 2078	Communication link, telemetry expander	6895	Linkage, front sway bar (Slash 4x4) (2) (assembled with rod ends, hollow balls and ball studs)
2978 2252	Fuse, D/C charger, 5A (2) (for #2974, 2975, 2977) Gear set, metal (for 2250, 2255 servos)	6897	Linkage, rear sway bar (Slash 4x4) (2) (assembled with rod ends,
2252 2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for	0007	hollow balls and ball studs)
2000/	Traxxas® iD® batteries)	5529	Shim set, 3x7x1mm (2), 3x6x0.5mm (4), 3x7x2mm (2)/ hollow balls,
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for		captured (4)
	Traxxas® iD® batteries)	6838	Shock tower, rear
6555	Mount, telemetry expander (fits Slash 4X4, Stampede® 4X4,	6838X	Shock tower, rear, 7075-T6 aluminum (blue-anodized) (1)/ body
	Rally, Jato®)		mount bracket (1)

Page 4 Stampede® 4X4: TQ™ 2.4GHz Radio (Model 67054-61) Parts List

6853X Stub av 6732 Susper 3x18ml 3655P Suspel 3655R Suspel 3655G Suspel 3655X Susper 3655T Suspel 3655L Suspel 6834 Susper	(assembled with internal-splined half shaft) kles, rear, heavy duty (2)/pins (2) nsion arm guards, front (2)/ guard spacers (2)/ hollow balls (2)/ m BCS (4) nsion arms, blue, front/rear (left & right), heavy duty (2)	2664 5862	Big Bore shock cylinder (long) (1) Big Bore shocks (hard-anodized & PTFE-coated T6 aluminum)
6732 Susper 3x18mi 3655P Suspei 3655R Suspei 3655G Suspei 3655X Susper 3655T Suspei 3655L Suspei 6834 Susper	nsion arm guards, front (2)/ guard spacers (2)/ hollow balls (2)/ m BCS (4) nsion arms, blue, front/rear (left & right), heavy duty (2)		
3x18mi 3655P Suspei 3655R Suspei 3655G Suspei 3655X Susper 3655T Suspei 3655L Suspei 3834 Susper	m BCS (4) nsion arms, blue, front/rear (left & right), heavy duty (2)		
3655R Suspen 3655G Suspen 3655X Suspen 3655T Suspen 3655L Suspen 6834 Suspen		2660	(assembled with TiN shafts and springs) (front & rear) (4) Big-bore shocks (long) (hard-anodized & PTFE-coated T6
3655G Susper 3655X Susper 3655T Susper 3655L Susper 3634 Susper	nsion arms, front/rear (left & right), heavy duty (2)		aluminum) (assembled with TiN shafts) w/o springs (rear) (2)
3655T Suspension 3655L Suspension 5834 Suspension	nsion arms, green, front/rear (left & right), heavy duty (2)	2662	Big-bore shocks (xx-long) (hard-anodized & PTFE-coated T6
3655L Suspe i 6834 Susper	nsion arms, left & right	2669	aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushing
6834 Susper	nsion arms, orange, front/rear (left & right), heavy duty (2)	2003	& washers (2) (Big Bore Shocks)
	nsion arms, red, front/rear (left & right), heavy duty (2)	1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screw
	nsion pin set, complete (front and rear) bar kit (front and rear) (includes front and rear sway bars		(2)
•	ljustable linkage)	2742X	Rod ends, short (6)/ hollow balls (6)
	uckles, camber link, 39mm (69mm center to center)	2667 2362	Shock caps, aluminum (2) (Big Bore Shocks) Shock rebuild kit (for 2 shocks)
•	nbled with rod ends and hollow balls) (1 left, 1 right)	1664T	Shock shafts, hardened steel, titanium nitride coated (long) (2)
6896 Wires, (4)	sway bar (front & rear, hard & soft) (Slash 4X4)/ 3x6 FCS	2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long) (2)
	Shock Oil	1664	Shock shafts, steel, chrome finish (long) (2)
5031 Oil, sh	ock (20 wt, 200 cSt, 60cc) (silicone)	2656	Shock shafts, steel, chrome finish (xx-long) (2)
•	ock (30 wt, 350 cSt, 60cc) (silicone)	1765	Silicone diaphragms (4)
•	ock (40 wt, 500 cSt, 60cc) (silicone)	2668	Spring retainers, upper & lower (2)/ spring pre-load spacers:
,	ock (50 wt, 600 cSt, 60cc) (silicone)		1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks)
•	ock (60 wt, 700 cSt, 60cc) (silicone)	6863	Springs, front (progressive, +10% rate, pink) (2)
•	ock (70 wt, 900 cSt, 60cc) (silicone) ock (80 wt, 1,000 cSt, 60cc) (silicone)	6864	Springs, front (progressive, +20% rate, blue) (2)
, -	oil bottle (60cc) (for mixing shock oil)	6862	Springs, front (progressive, -10% rate, green) (2)
	oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &	6861	Springs, front (progressive, -20% rate, orange) (2)
	premium shock oils with spinning carousel rack)	6857	Springs, front (white) (progressive rate) (2)
5038 Spinni	ng carousel rack	5860	Springs, front (white) (progressive rate) (2) (for Slash big bore shocks)
	Shocks (GTR)	6867	Springs, rear (progressive, +10% rate, pink) (2)
•	GTR long (hard-anodized, PTFE-coated aluminum) (1)	6868	Springs, rear (progressive, +20% rate, blue) (2)
7466 Body, bodies	GTR long shock, aluminum (blue-anodized) (PTFE-coated	6866	Springs, rear (progressive, -10% rate, green) (2)
	GTR long shock, aluminum (green-anodized) (PTFE-	6865	Springs, rear (progressive, -20% rate, orange) (2)
	I bodies) (1)	6858 5859	Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) (for Slash big bore
	GTR long shock, aluminum (orange-anodized) (PTFE- l bodies) (1)	3033	shocks)
7467X Body,	GTR xx-long (hard-anodized, PTFE-coated aluminum) (1)		Shocks (Ultra Shocks)
•	GTR xx-long shock, aluminum (blue-anodized) (PTFE-	3642	Attachment screws, shock (3x12mm shoulder screws) (6)
	l bodies) (1)	3765A	Body, Ultra Shock (long) (grey) (2)
	GTR xx-long shock, aluminum (green-anodized) (PTFE- l bodies) (1)	3766A 1942	Body, Ultra Shock (XXL) (grey) (2) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screw
	GTR xx-long shock, aluminum (orange-anodized) (PTFE-	1342	(2)
•	l bodies) (1)	2742X	Rod ends, short (6)/ hollow balls (6)
	& spring retainers, GTR shock (upper cap (2)/ hollow balls	3767	Shock caps (2)/ shock bottoms (2)
	ttom cap (2)/ upper retainer (2)/ lower retainer (2))	3767A	Shock caps, aluminum (blue-anodized) (4) (fits all Ultra Shocks)
	and spring retainers, GTR long/xx-long shock (upper cap llow balls (4)/ bottom cap (2)/ upper retainer (2)/ lower	3767G 3767T	Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks Shock caps, aluminum (orange-anodized) (4) (fits all Ultra
	ool (plastic)	3767P	Shocks) Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)
	2.5mm nylon locking (12)	3767X	Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)
7463 Rebuil	d kit, GTR long/xx-long shocks (x-rings, bladders, pistons,	2362	Shock rebuild kit (for 2 shocks)
	nuts, shock rod ends, hollow balls) (renews 2 shocks)	1664T	Shock shafts, hardened steel, titanium nitride coated (long) (2)
	nds (GTR shocks)	2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)
	GTR long, TiN-coated (2)		(2)
	s, GTR long blue-anodized, PTFE-coated bodies with TiN (fully assembled, without springs) (2)	1664	Shock shafts, steel, chrome finish (long) (2)
	s, GTR long green-anodized, PTFE-coated bodies with TiN	2656	Shock shafts, steel, chrome finish (xx-long) (2)
	(fully assembled, without springs) (2)	1765 3769	Silicone diaphragms (4) Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2)
	s, GTR long, hard-anodized, PTFE-coated bodies with TiN (assembled) (2) (without springs)	3768	Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hol (2))
	s, GTR xx-long blue-anodized, PTFE-coated bodies with afts (fully assembled, without springs) (2)	3758	Springs (front) (2)
	s, GTR xx-long green-anodized, PTFE-coated bodies with afts (fully assembled, without springs) (2)	3758T 3757T	Springs, blue (front) (2) Springs, blue (rear) (2)
7462X Shocks	s, GTR xx-long, hard-anodized, PTFE-coated bodies with afts (assembled) (2) (without springs)	6863 6864	Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2)
	retainers, lower (captured) (4)/ 2.5x10 CS (4)	6862	Springs, front (progressive, -10% rate, green) (2)
	, shock, white (GTR long) (0.623 rate orange) (1 pair)	6861	Springs, front (progressive, -20% rate, orange) (2)
7441 Spring	, shock, white (GTR long) (0.653 rate green) (1 pair)	6857	Springs, front (white) (progressive rate) (2)
7444 Spring	, shock, white (GTR long) (0.767 rate black) (1 pair)	3758A	Springs, green (front) (2)
	, shock, white (GTR long) (0.810 rate pink) (1 pair)	3757A 3758P	Springs, green (rear) (2) Springs, pink (front) (2)
	, shock, white (GTR long) (0.892 rate blue) (1 pair)	3757P	Springs, pink (non) (2) Springs, pink (rear) (2)
	, shock, white (GTR xx-long) (0.711 rate orange) (1 pair)	3757	Springs, rear (black) (2)
/AAK Chrina	ı, shock, white (GTR xx-long) (0.762 rate green) (1 pair) ı, shock, white (GTR xx-long) (0.874 rate black) (1 pair)	6867	Springs, rear (progressive, +10% rate, pink) (2)
	, shock, white (GTR xx-long) (0.884 rate black) (1 pair)	6868	Springs, rear (progressive, +20% rate, blue) (2)
7446 Spring	, SHOCK, WHILE (GIR AX-IOHU) (0.004 late Dillk) (1 Dail)		
7446 Spring 7447 Spring	, shock, white (GTR xx-long) (0.004 rate plink) (1 pair)	6866 6865	Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2)

858 957	Springs, rear (white) (progressive rate) (2) Springs, red (for Ultra Shocks only) (2.5 rate) (f/r) (2)	6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering
758X	Springs, white (front) (2)	6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronge
757X 760	Springs, white (rear) (2) Ultra Shocks (black) (long) (complete w/ spring pre-load spacers	6742G	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1) Toe links (TUBES green-anodized, 7075-T6 aluminum, strong
762	& springs) (front) (2) Ultra Shocks (black) (xx-long) (complete w/ spring pre-load	6742R	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
760A	spacers & springs) (rear) (2) Ultra Shocks (grey) (long) (complete w/ spring pre-load spacers &	2746	Washers, 3x6mm metal (12)
00/1	springs) (2)		Suspension Linkage
762A	Ultra Shocks (grey) (xx-long) (complete w/ spring pre-load spacers &	2537	3mm threaded rods: 1 each of 20mm,25mm&44mm
	springs) (rear) (2)	3641A	Camber link set (plastic / non-adjustable) (front & rear) (grey)
	Slipper Clutch Components	3641	Camber link set (plastic/ non-adjustable) (front & rear) (black
93X	Bearing adapter, 6061-T6 aluminum (blue-anodized) (1)/10x15x4mm ball bearing (black rubber sealed) (1) (for slipper shaft)	3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminu stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
93G	Bearing adapter, 6061-T6 aluminum (green-anodized) (1)/ 10x15x4mm ball bearing (black rubber sealed) (1) (for slipper	3643G	Camber links, front (TUBES green-anodized, 7075-T6 alumin stronger than Titanium) (83mm) (2)/ rod ends (4)/ aluminum
14.4	shaft)	26425	wrench (1) (#2579 3x15 BCS (4) required for installation)
1 14 888	Differential kit, center (complete)	3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminur stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
88X	Drive hub, center, rear (1)/ 4x3 GS (1) Drive hub, front, hardened steel (1)/ screw pin (1)		wrench (1) (#2579 3x15 BCS (4) required for installation)
383	Gear set, center differential (output gears (2)/ spider gears (2)/	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminur
	spider gear shaft)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
384	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/	26446	wrench (1) (#2579 3x15 BCS (4) required for installation)
393	bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/ pin (1)	3644G	Camber links, rear (TUBES green-anodized, 7075-T6 aluming stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
วยง 352R	Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum		wrench (1) (#2579 3x15 BCS (4) required for installation)
	friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL	3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum
	(1)/ 4.0mm NL (1))		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
52X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (1)/	5525	wrench (1) (#2579 3x15 BCS (4) required for installation) Rod ends (12)/ hollow balls (12)
552X	2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/	2742	Rod ends, long (6)/ hollow ball connectors (6)
,0 <u>-</u> 2,	pin/ 4.0mm NL (1)/ 5.0mm NL (1))	5529	Shim set, 3x7x1mm (2), 3x6x0.5mm (4), 3x7x2mm (2)/ hollow be
54	Screws, 3x6mm caphead machine (hex drive) (6)	0004	captured (4)
378	Slipper clutch, complete (for Slash 4x4)	6834 6742X	Suspension pin set, complete (front and rear) Toe links (TUBES blue-anodized, 7075-T6 aluminum, strong
556 851	Slipper pressure plate & hub (aluminum alloy) Slipper pressure plate and hub (alloy)	01427	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1
JJ 1		6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stron
	Spur Gears & Pinion Gears	07.400	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1
'47)42X	Gear, 11-T pinion (32-p) (steel) (fits 3mm shaft)/ set screw Gear, 12-T pinion (32-p), heavy duty (machined, hardened steel)	6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronge than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1
7427	(fits 3mm shaft)/ set screw	2335	Turnbuckles (72mm) (Tie rods or optional rear camber rods) (2)
43X	Gear, 13-T pinion (32-p), heavy duty (machined, hardened steel) (fits 3mm shaft)/ set screw	3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right)
944X	Gear, 14-T pinion (32-p), heavy duty (machined, hardened steel) (fits 3mm shaft)/ set screw	3643	Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right)
)45X)46X	Gear, 15-T pinion (32-p), heavy duty (machined, hardened steel) (fits 3mm shaft)/ set screw Gear, 16-T pinion (32-p), heavy duty (machined, hardened steel)	5539	Turnbuckles, camber links, 58mm (assembled with rod end- hollow balls) (2)
707	(fits 3mm shaft)/ set screw		Team Traxxas Items
47X	Gear, 17-T pinion (32-p), heavy duty (machined, hardened steel)	2514	Decal sheet, racing sponsors
140V	(fits 3mm shaft)/ set screw	6160X 9950	DVD, Maxx® Power! Full Throttle Action (sleeve) Official Team Traxxas® racing decal set(flag logo/ 6-color)
48X	Gear, 18-T pinion (32-p), heavy duty (machined, hardened steel) (fits 3mm shaft)/ set screw	9909	Traxxas® racing banner, red & black (3x7 feet)
949X	Gear, 19-T pinion (32-p), heavy duty (machined, hardened steel)		Tires & Wheels
	(fits 3mm shaft)/ set screw	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
950X	Gear, 20-T pinion (32-p), heavy duty (machined, hardened steel) (fits 3mm shaft)/ set screw	5854	Hub retainer, 17mm hubs, M4 X 0.7 (4) (use with #5853X, #6
951X	Gear, 21-T pinion (32-p), heavy duty (machined, hardened steel)		#6469)
	(fits 3mm shaft)/ set screw	1747P	Nuts, 4mm flanged nylon locking (aluminum, pink anodized
952X	Gear, 22-T pinion (32-p), heavy duty (machined, hardened steel)	3647 1747R	Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4
' 45	(fits 3mm shaft)/ set screw Gear, 9-T pinion (32-p) (steel) (fits 3mm shaft)/ set screw	1747G	Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (
45 342	Spur gear, 50-tooth (0.8 metric pitch, compatible with 32-pitch)	1747T	Nuts, aluminum, flanged, serrated (4mm) (orange-anodized)
342R	Spur gear, 50-tooth (0.8 metric pitch, compatible with 32-pitch) (for Slash 4x4 center differential)	1985 1647	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings Silicone Grease
43	Spur gear, 52-tooth (0.8 metric pitch, compatible with 32-pitch)	2754	Stub axle pins (4)
843R	Spur gear, 52-tooth (0.8 metric pitch, compatible with 32-pitch) (for Slash 4x4 center differential)	4175	Tires & wheels, assembled, glued (2.8") (All-Star black chro wheels, paddle tires, foam inserts) (nitro rear/electric front) (TSM® rated)
56 56R	Spur gear, 54-tooth (0.8 metric pitch, compatible with 32-pitch) Spur gear, 54-tooth (0.8 metric pitch, compatible with 32-pitch) (for center differential)	3669A	Tires & wheels, assembled, glued (2.8") (All-Star black chrowheels, Talon tires, foam inserts) (nitro rear/electric front) (3.8)
56X	Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-	3669	(TSM® rated) Tires & wheels, assembled, glued (2.8") (All-Star chrome wh
	pitch) (for center differential)	5503	Talon tires, foam inserts) (nitro rear/electric front) (2)
	Steering Components	6792	Tires & wheels, assembled, glued (black 2.8" wheels,
552	3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1)	20057	Sledgehammer® tires, foam inserts) (2) (TSM® rated)
1 4 545	Ball bearings, blue rubber shield (5x8x2.5mm) (2) Bushings (plastic) (5x8x2.5mm) (4)	3665X	Tires & wheels, assembled, glued (chrome wheels, Terra Gr dual profile tires, foam inserts) (nitro rear/ electric front) (2)
346	Linkage, steering (Revo) (3x20mm turnbuckle) (1)/ rod ends (2)/	3665	Tires & wheels, assembled, glued (satin chrome wheels, Te
	hollow balls (2)		Groove dual profile tires, foam inserts) (nitro rear/ electric fi

Page 6 Stampede® 4X4: TQ™ 2.4GHz Radio (Model 67054-61) Parts List

6771	Tires and wheels, assembled, glued 2.8" (All-Star chrome wheels,	6742G
	Maxx® tires, foam inserts) (2)	
6770	Tires, Maxx® 2.8" (2)/ foam inserts (2)	6742R
3671	Tires, Talon 2.8" (2)/ foam inserts (2)	
1654	Wheel hubs, hex (2)/ stub axle pins (2)	2335
1654X	Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle pins(2)	3644
6856X	Wheel hubs, splined, 17mm, short (blue-anodized) (4)/ wheel nuts, splined, 17mm (blue-anodized) (4)/ hub retainer M4 X 0.7	3643
	(4)/ axle pin (4) (Slash 4WD)	5539
5353	Wheel nuts, splined, 17mm (blue-anodized) (4)	
5480X	Wheel wrench, splined, 17mm	
5576A	Wheels, All-Star 2.8" (black chrome) (nitro rear / electric front) (2)	
5576	Wheels, All-Star 2.8" (chrome) (nitro rear / electric front) (2)	
5572	Wheels, Jato® twin-spoke 2.8" (chrome) (rear) (2)	
	Traxxas Tools	
3433Y	Rody reamer (aluminum handle)	

Body reamer (aluminum handle) 3433 Body reamer (plastic handle) 3436 Cap, body reamer 3432 Scissors, curved tip 3431 Scissors, straight tip 8712 Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive Speed bit handle, large (overmolded) 8720 8721 Speed bit handle, medium (one piece) 8722 Speed bit handle, premium (rubber overmold) 8710 Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive 8711 Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive 8719 Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive 8716 Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" 8716X Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 8715 2.5mm), 1/4" drive 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2748R 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint

Turnbuckles & Threaded Rods

Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,

3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm

wrench)

wrenches/ driver handle)

3415

	I di iliadokioo & i ili oddod ilodo
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
	wrench (1) (#2579 3x15 BCS (4) required for installation)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than Titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3644G	Camber links, rear (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
5525	Rod ends (12)/ hollow balls (12)
2742	Rod ends, long (6)/ hollow ball connectors (6)
5529	Shim set, 3x7x1mm (2), 3x6x0.5mm (4), 3x7x2mm (2)/ hollow balls, captured (4)
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)

Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
Turnbuckles (72mm) (Tie rods or optional rear camber rods) (2)
Turnbuckles, camber link, 39mm (69mm center to center)
(assembled with rod ends and hollow balls) (1 left, 1 right)
Turnbuckles, camber link, 49mm (82mm center to center)
(assembled with rod ends and hollow balls) (1 left, 1 right)
Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM